

Sealing Wax Protection - Standard Protection -

Product Description

Menzerna Sealing Wax Protection is the basic coating sealant. It protects the surface against environmental influences and deposits.

| | | |
|---|---|---|
| <p>General information:</p> <p>Product Group: Protection</p> <p>Application: Detailing</p> <p>Service life: approx. 2-4 weeks</p> <p>Storage: 5-30°C, avoid frost and direct sunlight</p> <p>Colour: Yellow</p> <p>Volumes: 250 ml: 22870.281.001 1 L: 22870.261.001</p> | <p>Chemical information:</p> <p>Density: 1,0 kg/l</p> <p>Viscosity: 2-7 Pas</p> |  |
| | <p>Technical information:</p> <p>Polishing tool: Wax Foam Pad</p> <p>Speed recommendation for hard paints: Orbital: lower speed range (also manual usage with Hand Applicator or Microfiber Towel possible)</p> <p>Pressure recommendation: Low pressure</p> | |

Recommended Usage

- Clean surface thoroughly prior to polishing.
- Shake the bottle prior to use and apply the following quantity of the product onto the polishing pad.
Recommendation for a 40cm x 40cm area:
Pad with a diameter of 95mm: 3-4 pea-sized drops
Pad with a diameter of 150mm: 5 pea-sized drops
Pad with a diameter of 180mm: 6-7 pea-sized drops
- Use the Menzerna Wax Foam Pad in the event of heavy signs of use.
- Use an orbital polishing machine and use the cross-coating method.
Apply light, even pressure while polishing and extend the product with a constant low machine speed.
- At first, the polish will seem a little milky and should be worked in until only a slightly transparent/oily film is visible.
- Leave the sealant to dry for 5 to 10 minutes and remove any residual polish with the Premium Microfiber Cloth, without applying any pressure.

Important notice:

All the information above is based on our empirical values. Please test the use of our product yourself to determine whether it is suitable for your intended application. All matters related to the warranty and liability for this product are governed by our general selling terms and conditions, unless otherwise specified by applicable legal regulations.

How to find us:

Menzerna Polishing Compounds GmbH & Co KG
Industriestr. 25, D-76470 Ötigheim
Tel.: +49-7222-9157-0
office@menzerna.com

Menzerna Polishing Programm

| | 1. Heavy Cut | 2. Medium Cut | 3. Finish | 4. Protection |
|----------------------|-----------------------------|---------------------|--------------------------|---------------------|
| Standard Products | HCC1000 | MCP2500 | FF3000 | Power Lock Ultimate |
| Alternative Products | HCC1100 | MCP2400 | SF3500 | Liquid Carnauba |
| | | MCP2200 | SFP3800 | Sealing Wax |
| Premium Products | SHCC300/ SHCC300 GREEN LINE | | Power Protect Ultra 2in1 | |
| | HCC400/ HCC400 GREEN LINE | | | |
| | One-Step Polish 3in1 | | | |
| Premium Pads | Wool/ Heavy Cut Pad | Medium Cut Foam Pad | Soft Cut Foam Pad | Wax Foam Pad |

Important notice:

All the information above is based on our empirical values. Please test the use of our product yourself to determine whether it is suitable for your intended application. All matters related to the warranty and liability for this product are governed by our general selling terms and conditions, unless otherwise specified by applicable legal regulations.

How to find us:

Menzerna Polishing Compounds GmbH & Co KG
 Industriestr. 25, D-76470 Ötigheim
 Tel.: +49-7222-9157-0
office@menzerna.com